

C52180 Phosphorus Bronze

C52180 is a Phosphor Bronze which is well known for its high strength. With greater tin content C52180 has exceptional bearing, wear and spring properties together with excellent fatigue properties and corrosion fatigue resistance. C52180 is widely used in marine and other corrosive environments.



C52180 Phosphorus Bronze

[:: Send Enquiry](#)

PDF



[DOWNLOAD PDF](#)

Equivalent Specifications:

Specifications	ASTM	BS	EN	JIS	DIN	ISO	IS
Designations	C52180	-	CW460K	Z3441(93) YCuSn B	-	CuSn8P	-

Chemical Composition:

	Cu	Pb	Sn	Zn	Fe	P	Ni
Min			7.0		0.05	0.01	0.05
Max	Rem	0.05	9.0	0.30	0.20	0.35	0.20

Specifications:

Product	Specification
Strip	ASTM B888/B88M

Fabrication Properties:

Joining Technique	Suitability
Soldering	Excellent
Brazing	Excellent
Oxyacetylene Welding	Fair

Gas Shielded Arc Welding	Good
Coated Metal Arc Welding	Fair
Spot Weld	Good
Seam Weld	Fair
Butt Weld	Excellent
Capacity for Being Cold Worked	Good
Machinability Rating	20

Physical Properties:

Melting Point - Liquidus	1880 °F
Melting Point - Solidus	1620 °F
Density	0.318 lb/cu in. at 68°F
Specific Gravity	8.8
Electrical Conductivity	13 % IACS at 68°F
Thermal Conductivity	36 Btu/ sq ft/ ft hr/ °F at 68°F
Coefficient of Thermal Expansion 68-572	10.1 10 ⁻⁶ per °F (68 – 572°F)
Modulus of Elasticity in Tension	16000 ksi
Modulus of Rigidity	6000 ksi

Sizes Available:

TUBES	6.35 mm to 110mm
ROUND WIRES	1 mm to 11mm
ROUND RODS	1.2 to 250 mm
HEX RODS	Min. 5 mm to Max. 60 mm
SQUARE RODS	Min. 4 mm to Max. 60 mm
FLATS	Min. 4 mm thickness and max width of 120mm
PROFILES	As per customer drawings
HOLLOW RODS	Min Bore Size 20mm and Max OD 130mm