

SHREE EXTRUSIONS LIMITED



UNS C77400 is a nickel-silver copper alloy. Its silvery appearance makes it a highly sought after metal in the jewelry and ornamental areas. Copper alloys are known for their corrosion resistance and tarnish-free surface.

TYPICAL APPLICATIONS:

Product Category

Architecture: Elevator Trim, Handrails, Thresholds

CHEMICAL COMPOSITION

	Cu	Pb	Zn	Ni
Min./Max.	43.0-47.0	009	Rem	9.0-11.0

PHYSICAL PROPERTIES

Densitylb/cu in. at 68°F	0.306
Specific Gravity	8.47

SIZES AVAILABLE:

HOLLOW RODS Min Bore Size 20 mm and Max OD 100 mm

ROUND RODS/BARS 6mm To 130 mm HEX 5mm To 60mm SQUARE 4mm To 60mm

5mm Min Thickness and max Width 120mm FLAT AS per Customer Drawing

PROFILES / SECTIONS BILLETS Up to 200 mm INGOTS AS per Specification

Regd. Office & Works: 217/218 Phase-II, Okha Rajkot Road, Dared, Jamnagar - 361 004. INDIA

Tel.: +91 - 288 - 2730118 | Mobile: +91 - 9328105172 mail@shree-extrusion.com I www.shree-extrusion.com



