

C69300 Lead-free ECO BRASS. It is a great replacement for leaded fittings and its corrosion resistance properties make it an excellent solution for water supply and plumbing applications. also has good machinability, excellent hot forgeability, easily accepts solder and brazing, and has excellent polishing and plating capabilities.

TYPICAL USES for C86300 High Tensile Manganese Bronze:

Industrial: Plumbing: Stop Valves, PEX fittings, Ball valves, Commercial and Residential water faucet parts. Automotive: Fluid Connectors, Sensor Bodies, Thermostat Parts. Industrial: Automatic Screw Machine Parts, Bolts, Condenser Tube Plate, Nuts, Pneumatic Fittings, Pump Parts, Screw Machine Product, Valve Stems, Valve Bodies for Water.

CHEMICAL COMPOSITION

| | Cu | Pb | Sn | Zn | Fe | Ni | Р | Si | Mn |
|-----|------|------|------|-----|------|-----|------|-----|------|
| Min | 73.0 | - | - | - | - | - | 0.04 | 2.7 | - |
| Max | 77.0 | 0.09 | 0.20 | Rem | 0.10 | 0.1 | 0.15 | 3.4 | 0.10 |

PHYSICAL PROPERTIES

| Melting Point – Liquidus °F | 1616 |
|---|-------|
| Melting Point – Solidus °F | 1571 |
| Density lb./cu in. at 68°F | 0.3 |
| Specific Gravity | 8.3 |
| Electrical Conductivity*% IACS at 68°F | 8 |
| Thermal Conductivity Btu/ sq. ft/ ft.Hr/ °F at 68°F | 21.8 |
| Coefficient of Thermal Expansion 68-57210 ⁻⁶ per °F (68 – 572°F) | 10.4 |
| Specific Heat Capacity Btu/ lb. /°F at 68°F | 0.09 |
| Modulus of Elasticity in Tension (ksi) | 15200 |

SIZES AVAILABLE:

ROUND RODS HEX SQUARE FLAT BILLETS INGOTS 1.2 mm to 250 mm5 mm to 65 mm4 mm to 60 mm4 mm Min Thickness and max Width 120 mmUp to 200 mmAs per Specification

Regd. Office & Works: 217/218 Phase - II Okha Rajkot Road, Dared, Jamnagar - 361 004. INDIA Tel.: +91 - 288 - 2730118 | Mobile: +91 - 9328105172 mail@shreeextrusion.com | www.shree-extrusion.com



NABL / ISO : 15189 Accreditation Number M - 0000

Quality, Technology & Vision at it's Best...